

G
K
B

Kleingüteraufzüge

Service lifts

Monte-plats

Małe dźwigi towarowe



Service lifts

EN 81-3/machinery directive 2006/42/EC

Basic information:

- Capacity 5 – 300 kg
- Up to 3 entrance sides
- Shaft doors as sliding, hinged, double hinged or combination of these landing doors available
- Doors on serving height or at floor level
- Motor position at the top, bottom or beside
- Nominal speed from 0.2 to 1.0 m/s
- Optionally safety gear for accessible space below the shaft

Car sizes:

- Width: 350 – 1000 mm
- Depth: 320 – 1000 mm
- Height: 600 – 1200 mm

Basic features:

- Car and landing doors with Zintec steel for individual color design by the customer
- Galvanized structure for the installation in a supporting shaft. Quick and easy installation by pre-assembled components
- Motor with compact worm gear
- Plug-and-play microprocessor controls, completely pre-wired, low voltage engineering
- Call and send control with position indicator
- Call acknowledgement and arrival buzzer
- Diagnostic system
- Documentation in more than 20 European Community languages

Optionally:

- Up to 30 stops
- Travel up to 120 m
- Landing doors fire-rated acc. to EN 81-58: E120, EW60, EI90
- Car doors resp. load securing techniques
- VVVF drive
- Car and shelf heater
- LED car lighting
- LED shaft lighting
- Overload device
- Automatic shaft doors
- Different materials and designs acc. to customer's demands
- Intercoms
- Ship and offshore lifts
- Water/dust ingress protection (IP)
- Special solutions for reduced space
- Other tailor made solutions on request

