

G

K

B

Güteraufzüge mit Montagegerüst

Goods lifts with auxiliary structure

Monte-charges avec pylône non-autoporteur

Dźwigi towarowe z konstrukcją szybu przewidzianą do obudowania



Goods lifts

EN 81-31 / machinery directive 2006/42/EC

Basic information:

- Capacity 300 – 1000 kg
- Up to 3 entrance sides
- Travel up to 12 m
- Single or double hinged landing doors
- Motor position at the top or beside
- Nominal speed from 0.1 to 0.3 m/s
- Safety gear for car
- Optionally safety gear on tension or balance weights for accessible space below the shaft

Car sizes:

- Width: 800 – 2000 mm
- Depth: 800 – 2000 mm
- Height: 1300 – 2000 mm

Basic features:

- Car and landing doors galvanized
- Galvanized structure for the installation in a supporting shaft.
Quick and easy installation by pre-assembled components
- Motor with compact worm gear
- Plug-and-play microprocessor controls, completely pre-wired, low voltage engineering
- Call and send control including key switch for restricted access
- Call acknowledgement, arrival buzzer and position indicator
- Diagnostic system
- LED car lighting
- LED shaft lighting
- Documentation in more than 20 European Community languages

Optionally:

- Landing doors fire-rated acc. EN 81-58: E120, EW60, EI90
- Car enclosure resp. load securing techniques
- VVVF drive
- Overload device
- Different materials and designs acc. to customer's demands
- Intercoms
- Ship and offshore lifts
- Water/dust ingress protection (IP)
- Special solutions for reduced space
- Other tailor made solutions on request

