

G

K


B

Güteraufzüge
mit selbsttragendem Gerüst

Goods lifts
with self-supporting structure

Monte-charges
avec pylône autoporteur

Dźwigi towarowe
z samonośną konstrukcją szybu



Goods lifts

EN 81-31 / machinery directive 2006/42/EC

Basic information:

- Capacity 300 – 2000 kg
- Up to 3 entrance sides
- Travel up to 12 m
- Single or double hinged landing doors
- Motor position at the top or beside
- Nominal speed from 0.1 to 0.3 m/s
- Safety gear for car
- Optionally safety gear on tension or balance weights for accessible space below the shaft

Car sizes:

- Width: 800 – 2000 mm
- Depth: 800 – 2000 mm
- Height: 1300 – 2000 mm

Basic features:

- Car and landing doors galvanized
- Self-supporting galvanized structure
- Motor with compact worm gear
- Plug-and-play microprocessor controls, completely pre-wired, low voltage engineering
- Call and send control including key switch for restricted access
- Call acknowledgement, arrival buzzer and position indicator
- Diagnostic system
- LED Car lighting
- LED Shaft lighting
- Documentation in more than 20 European Community languages

Optionally:

- Cladding for the structure
- Car enclosure resp. load securing techniques
- VVVF drive
- Overload device
- Different materials and designs acc. to customer's demands
- Intercoms
- Ship and offshore lifts
- Water/dust ingress protection (IP)
- Special solutions for reduced space
- Other tailor made solutions on request

