

**G
K
B**

**Güteraufzüge
mit Begleitperson**

**Goods lifts
with attendant**

**Monte-charges avec
accompagnement**

**Dźwigi towarowe
z możliwością jazdy
osoby uprawnionej**



Goods lifts with attendant

Machinery directive 2006/42/EC with EC-type examination

Basic information:

- Capacity 500 – 1500 kg
- Up to 3 entrance sides
- Travel up to 12 m
- Single or double hinged landing doors
- Motor position at the top or beside
- Nominal speed from 0.1 to 0.15 m/s
- Safety gear for car
- Optionally safety gear on tension or balance weights for accessible space below the shaft

Car sizes:

- Width: 800 – 2000 mm
- Depth: 1100 – 2000 mm
- Height: 2000 mm

Basic features:

- Car and landing doors galvanized
- Self-supporting galvanized structure
- Motor with compact worm gear
- PLC control unit, completely pre-wired, low voltage engineering
- Call and send control including key switch for restricted access
- Inside car control as constant pressure control activated by key switch
- Call acknowledgement, arrival buzzer and position indicator
- Diagnostic system
- LED car lighting with emergency lighting
- Continuous load guard between shaft doors
- Car entrance with light curtain
- LED shaft lighting
- Documentation in more than 20 European Community languages

Optionally:

- Cladding for the structure
- Preparation for autodialler by the customer
- VVVF drive
- Overload device
- Different materials and designs acc. to customer's demands
- Intercoms
- Water/dust ingress protection (IP)
- Special solutions for reduced space
- Other tailor made solutions on request

